

WAC LIGHTING

Bliss

Bathroom Sconce 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-79622 22"	3000K	PN Polished Nickel	31W	2600	1500

Example: **WS-79622F-35-PN**

•For 277V special order, add an "F" before the finish: WS-79622F-PN

For custom requests please contact customs@wacighting.com

FEATURES

- Conversion plate for 4" J box included
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed

REPLACEMENT PARTS

RPL-GLA-79622 - Glass for WS-79622




FINISHES:



Polished
Nickel

LINE DRAWING:



WAC LIGHTING

Bliss

Bathroom Sconce 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-79628 28"	3000K	PN Polished Nickel	40W	3600	2365

Example: **WS-79628F-35-PN**

•For 277V special order, add an "F" before the finish: WS-79628F-PN

For custom requests please contact customs@wacighting.com

FEATURES

- Conversion plate for 4" J box included
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty



SPECIFICATIONS


Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware, mitered glass diffuser with silk-screen exterior

FINISHES:



Polished
Nickel

LINE DRAWING:



WAC LIGHTING

Bliss

Bathroom Sconce 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-79636 36"	3000K	PN Polished Nickel	47W	4100	2800

Example: **WS-79636F-35-PN**

•For 277V special order, add an "F" before the finish: WS-79636F-PN

For custom requests please contact customs@wacighting.com

FEATURES

- Conversion plate for 4" J box included
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K
- Option to pre-select color temperature or adjust in the field
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware, mitered glass diffuser with silk-screen exterior

REPLACEMENT PARTS

RPL-GLA-79636 - Glass for WS-79636



FINISHES:



Polished
Nickel

LINE DRAWING:

