

# WAC LIGHTING

## Caliber

### Outdoor Wall Sconce 3000K

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
WS-W36610 10" - 1 Light	3000K - 90	11W	560	AL Brushed Aluminum BK Black BZ Bronze

Example: **WS-W36610-BZ**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Light projection tuned with precision.

#### FEATURES


- Discrete cylinder with minimal mounting hardware
- Weather-resistant powder coated finish
- WS-W36614 is Up & down light, WS-W36610 is one direction
- Light engine is factory sealed for maximum protection from the elements
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS


<b>Color Temp:</b>	3000K
<b>Input:</b>	120-277V,50/60Hz
<b>CRI</b>	90
<b>Dimming:</b>	ELV: 100-10%
<b>Rated Life:</b>	72,000 Hours
<b>Mounting:</b>	Can be mounted on wall vertically or horizontally
<b>Standards:</b>	ETL, cETL, IP65, ADA, Wet Location Listed
<b>Construction</b>	Aluminum hardware with lens diffuser



#### FINISHES:



#### LINE DRAWING:



WS-W36610

# WAC LIGHTING

## Caliber

### Outdoor Wall Sconce 3000K

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
WS-W36614 14" - 2 Lights	3000K - 90	21W	1140	AL Brushed Aluminum BK Black BZ Bronze

Example: **WS-W36614-BZ**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Light projection tuned with precision.

#### FEATURES


- Discrete cylinder with minimal mounting hardware
- Weather-resistant powder coated finish
- WS-W36614 is Up & down light, WS-W36610 is one direction
- Light engine is factory sealed for maximum protection from the elements
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS


<b>Color Temp:</b>	3000K
<b>Input:</b>	120-277V,50/60Hz
<b>CRI</b>	90
<b>Dimming:</b>	ELV: 100-10%
<b>Rated Life:</b>	72,000 Hours
<b>Mounting:</b>	Can be mounted on wall in all orientations
<b>Standards:</b>	ETL, cETL, IP65, ADA, Wet Location Listed
<b>Construction</b>	Aluminum hardware with lens diffuser



#### FINISHES:



#### LINE DRAWING:



WS-W36614