

WAC LIGHTING

Elementum

Bathroom Sconce 2700K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-7213 13"	2700K	BN Brushed Nickel CH Chrome	13W	1118	885

Example: **WS-7213F-BN**

• For 277V special order, add an "F" before the finish: WS-7213F-CH

• For alternate color temperature, special order adding 30 or 35: WS-7213F-35-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Tubular, streamlined design for adaptable vertical and horizontal oriented lighting. A sleek enhancement to any décor.

FEATURES

- A streamlined luminaire sealed to meet healthcare facility requirements
- 13" can only be mounted vertically
- Title 24 may not be available for all finishes, check for availability
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS


Color Temp:	2700K
Input:	120 VAC, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	80,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with mouth blown etched glass diffuser

REPLACEMENT PARTS


RPL-GLA-7213 - Glass for WS-7213



FINISHES:



LINE DRAWING:



WS-7213

WAC LIGHTING

Elementum

Bathroom Sconce 2700K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-7222 22"	2700K	BN Brushed Nickel CH Chrome	26W	2119	1590

Example: **WS-7222F-BN**

• For 277V special order, add an "F" before the finish: WS-7222F-CH

• For alternate color temperature, special order adding 30 or 35: WS-7222F-35-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Tubular, streamlined design for adaptable vertical and horizontal oriented lighting. A sleek enhancement to any décor.

FEATURES

- A streamlined luminaire sealed to meet healthcare facility requirements
- 13" can only be mounted vertically
- Title 24 may not be available for all finishes, check for availability
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS


Color Temp:	2700K
Input:	120 VAC, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	80,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with mouth blown etched glass diffuser

REPLACEMENT PARTS


RPL-GLA-7213 - Glass for WS-7222



FINISHES:



LINE DRAWING:



WS-7222