



Dimple Sconce

Sconces

YOUR PRODUCT CODE

DP-WS- - - - - - - - -

DESCRIPTION

Dimple is a compact and flush-mounted sconce that casts a diffuse and soft, atmospheric light. It is cheekily named for the thick, domed circular diffuser embedded into its front face. The Natural Anodized backplate finish on Dimple Sconces is not the same finish as the Natural backplate finish on Dimple Dash Sconces. The backplate on Dimple Sconces can be powder coated to more closely match the Natural finish on Dimple Dash Sconces.

575 Reiger Ln Kingston, NY 12401 T: 1 212 398 1621 sales@rbw.com

PERFORMANCE

Standard Output Power Consumption 8.5W
High-Output Power Consumption 17.4W
95 CRI (Smoked) 90 CRI (Frosted/White) 80 CRI (Amber)
Full detail in [photometry summary](#).

CERTIFICATION

ADA Compliant
UL Listed
UL Listed to Canadian safety standards.
Suitable for Wet Locations
Suitable for Damp Locations
IP20
IP65
Declare (LBC Red List Approved)

Declare.

LED LIFESPAN

50k hours

SPECIFICATION LOGIC

GLASS FINISH

White Interior	S1
Smoked	S2
Amber	S3
Frosted	S4

BACKPLATE FINISH

Natural Anodized	AA01
Black Anodized	AA04

COLOR TEMPERATURE

2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

DIMMING / CONTROL / INPUT

10% Dimming, TRIAC / Forward Phase Control, 120V Input	10_TRIAC_120V
1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	1_TRIAC_120V
1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	1_10V_UNV
0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	0.1_10V_UNV
High-Output, 1% Dimming, TRIAC / Forward Phase Control, 120V Input (Driver External)	HO_1_TRIAC_120V
High-Output, 1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	HO_1_10V_UNV
High-Output, 0.1% Dimming, 0-10V Control, 120V or 277V "Universal Input" (Driver External)	HO_0.1_10V_UNV
Low Voltage (Driver required, driver not included)	LV

MATERIALS

Cast solid glass, aluminum

COLLECTION NOTES

Luminaire lumens listed are for AC input TRIAC control. DC input performance please see photometry downloads. Each form of cast glass is unique. As part of the casting process, there may be small air bubbles within the glass. The Natural Anodized backplate finish on Dimple Sconces is not the same finish as the Natural Cast backplate finish on Dimple Dash Sconces. The backplate on Dimple Sconces can be powder coated to more closely match the Natural Cast finish on Dimple Dash Sconces. Contact us to special order a powder coated backplate.

PRODUCT DIMENSIONS

5 in dia x 3.3 in D

PRODUCT WEIGHT

3 lbs / 1.6 kg

DRAWINGS

IP 20	IP20
DP-WS Dimple Sconce Dimension	IP65

