PH 3½-3 PENDANT

Brass Metallised, 5741919675, Designed by Poul Henningsen

Type:	
Product:	
Project:	
Modified:	



Technical specifications

Materials
Shades: Hand-blown three-layered opal glass with sandblasted inner side.

Suspension: Drawn brass.

Finishes
Hand-blown three-layered opal glass with sandblasted inner side.

Brass Metallised, Black Metallised or High Lustre Chrome Plated.

Mounting
12'. 3-conductor, 18 AWG power cord.

Canopy included. For mounting instructions, see download section on the product detail page.

Information
Electrical:
System Wattage: 15W
LED Wattage: 14 W
Delivered lumens: 1,364
Efficacy: 90.9 lm/W

Certifications:
cULus, Dry Location
Protection class IP20
Controllability: Phase dimming
Actual performance dependent upon screw-base lamp used. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

PH 3½-3 PENDANT

Brass Metallised, 5741919675, Designed by Poul Henningsen

Type:	
Product:	
Project:	
Modified:	

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5741919675	1x15W A-19/medium	120V/60HZ	594		White fabric cord	Brass Metallised	13 / 11.3 / 13 in / 8.1 lb
5741919976	1x15W A-19/medium	120V/60HZ	594		Black fabric cord	BLACK METALIZED, 906	13 / 11.3 / 13 in / 8.0 lb
5741919989	1x15W A-19/medium	120V/60HZ	594		Black fabric cord	HIGH LUSTRE CHROME PLATED, 900	13 / 11.3 / 13 in / 8.0 lb