

WAC LIGHTING

Elementum

Mini Pendant

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-26611 11"	3000K	SN Satin Nickel	16W	1187	971

Example: **PD-26611-SN**•For alternate color temperature, special order adding 27 or 35: PD-26611-35-SN

For custom requests please contact customs@wacighting.com

DESCRIPTION

True chemistry between light and style.

FEATURES

- Twist lock glass attachment
- Slope ceiling adaptable. Hang straight swivel up to 90 degrees
- Three 12" and one 6" downrods included (additional downrods available)
- Evenly lit etched opal glass
- Simple form, big impact
- Driver installed within the Junction Box, driver dimension: 2.8" x 1.6" x 1.1"
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10%
Rated Life:	65,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

- RPL-ROD-IN06-SN - 6" rod - SN finish
RPL-ROD-IN12-SN - 12" rod - SN finish




FINISHES:



Satin Nickel

LINE DRAWING



WAC LIGHTING

Elementum

Mini Pendant

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-26616 16"	3000K	SN Satin Nickel	21W	1769	1369

Example: **PD-26616-SN**•For alternate color temperature, special order adding 27 or 35: PD-26616-35-SN

For custom requests please contact customs@wacighting.com

DESCRIPTION

True chemistry between light and style.

FEATURES

- Twist lock glass attachment
- Slope ceiling adaptable. Hang straight swivel up to 90 degrees
- Three 12" and one 6" downrods included (additional downrods available)
- Evenly lit etched opal glass
- Simple form, big impact
- Driver installed within the Junction Box, driver dimension: 2.8" x 1.6" x 1.1"
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , 0-10V: 100-10%
Rated Life:	65,000 Hours
Standards:	ETL, cETL, Title 24 JA8 Compliant, Damp Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

- RPL-ROD-IN06-SN - 6" rod - SN finish
RPL-ROD-IN12-SN - 12" rod - SN finish



FINISHES:



Satin Nickel

LINE DRAWING

