

WAC LIGHTING

Niveous

Ceiling And Wall Mount 3000K

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
○ FM-W52306 6"	3000K	○ WT White	10W	800	680

Example: **FM-W52306-WT**

•For 277V special order, add an "F" before the finish: FM-W52306F-WT

•For alternate color temperature, special order adding 27 or 35: FM-W52306F-35-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect sphere.

FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Wet Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

RPL-GLA-52306 - Glass for FM-W52306




FINISHES:



White

LINE DRAWING



WAC LIGHTING

Niveous

Ceiling And Wall Mount 3000K

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
☐ FM-W52309 9"	3000K	☐ WT White	18W	1600	1428

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **FM-W52309-WT**

•For 277V special order, add an "F" before the finish: FM-W52309F-WT

•For alternate color temperature, special order adding 27 or 35: FM-W52309F-35-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect sphere.

FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" x 1.2" x 0.5"
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K
Input:	120 VAC,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Wet Location Listed
Construction	Aluminum hardware with opal glass diffuser

REPLACEMENT PARTS

RPL-GLA-52309 - Glass for FM-W52309



FINISHES:



White

LINE DRAWING

